



Vertical packaging machine Mod. FP - T500

Ribbon: 500 mm. Capacity: 95 bags/ min.

Photocell for centering engine print Square bottom group



*four edged sealing does
a four sided seal bag*

TECHNICAL CHARACTERISTICS- CARATTERISTICHE TECNICHE

Type	FP T500	Tipo
Bag Front Width	70-180mm	Larghezza fronte confezione
Side Width	40-100mm	Larghezza lato confezione
width of side seal	5-10mm	Larghezza lato sigillatura
Length	100-350mm	Lunghezza
Bag shape	pillow pouch/ standing bag/ block bottom bag	Forma confezione
Packing speed	50bags/min	Velocità di confezionamento
Max measuring range	3000ml	Massima dose confezionabile
Air consumption	0.8mpa/ 0.3m/min	Consumo aria
foil thickness	0.04-0.08mm	Spessore bobina
Power voltage	220VAC/50Hz/ 3.5KW	Voltaggio
Max foil width	500mm	Massima larghezza bobina
Dimension	1300*1130*1900mm	Dimensioni
Weight	750kg	peso

PILLOW - INTEGRATED IN THE VFFS



The vacuum chamber for square bottom allows to realize "brick-like" bags, starting from a block bottom bag coming out of a VFFS.

The device receives a bag pre-sealed by the packaging machine and keeps it inside a dedicated space until previous vacuuming cycle is concluded. Next, it enters into the vacuum chamber, where a system of pushers driven by cylinders squares the bag and expels residual air. Heated sealing bars do the final closure.

Such system permits to increase production's speed, avoiding useless downtimes deriving from the product's dosing inside the packaging machine, which is instead done contemporarily to the vacuuming cycle.

- Performances up to 15 bpm
- Realized in anodized aluminum and stainless steel
- Rapid format changes
- Over 95% vacuum tightness
- Structure on wheels



VACUUM CHAMBER FOR SQUARE BOTTOM

